






# PHOENIX

50Sn/50Pb SOLID WIRE SOLDER




Phoenix is comprised of 50% Tin and 50% Lead. This alloy was the original Plumbing solder and is commonly used today for non-potable water and DWV (drain, waste and vent) applications due to its versatility, flow and low melting point.

## PACKAGING

Description	Phoenix 50Sn/50Pb Solid Leaded Wire Solder		
Part No.	4:20053	4:20054	4:20055
Spool Weight	1 lb / 454 g	5 lb / 2.27 kg	20 lb / 9.08 kg
Wire Diameter	0.118" / 3 mm		
Case Count	24	4	1
Item UPC Code			
Carton UPC Coded	Yes		

## LABEL



## FAST FACTS

Alloy: 50Sn/50Pb	Melting Range: 183 - 216 C 361 - 421 F	ASTM B32 Compliant	Indefinite Shelf Life	High-Purity Virgin Metals
Leaded	Ultimate Tensile Strength 9790 psi / 67.5 MPa		Usable with any Application- Compliant Flux	Made in the U.S.A

**Nathan Trotter & Co., Inc.**  
241 West Stewart Huston Drive  
Coatesville, PA 19320  
United States of America

**Contact**  
P 610.524.1440  
E [info@nathantrotter.com](mailto:info@nathantrotter.com)  
E [sales@nathantrotter.com](mailto:sales@nathantrotter.com)



Nathan Trotter  
Website



Nathan Trotter  
LinkedIn



Safety Data  
Sheet

**Quality Metals  
Since 1789**  
—  
[nathantrotter.com](http://nathantrotter.com)  
ISO 9001 • 2015 Registered